



TEHNIČKE KARAKTERISTIKE AUTOMOBILSKIH FOLIJA

Proizvod	Transmisija solarne energije	Refleksija solarne energije	Absorbicija solarne energije	Transmisija vidljive svjetlosti	Refleksija vidljive svjetlosti	Transmisija UV zračenja	Ukupna odbijena solarna energija
Esprit Serija ***						Garancija: 7 godina	
ATC 05 CH SR HPR	41%	6%	53%	5%	8%	< 1 %	44%
ATC 05 GR SR HPR	45%	7%	48%	7%	8%	< 1 %	42%
ATC 15 CH SR HPR	48%	6%	46%	20%	8%	< 1 %	39%
ATC 15 GR SR HPR	50%	7%	43%	16%	8%	< 1 %	39%
ATC 20 CH SR HPR	47%	7%	46%	23%	8%	< 1 %	39%
ATC 20 GR SR HPR	54%	7%	39%	25%	8%	< 1 %	35%
ATC 35 CH SR HPR	56%	5%	39%	37%	8%	< 1 %	33%
ATC 35 GR SR HPR	61%	7%	32%	40%	6%	< 1 %	30%
ATC 50 CH SR HPR	63%	7%	30%	54%	8%	< 1 %	29%
ATC 50 GR SR HPR	71%	8%	21%	59%	8%	< 1 %	23%
ATC 70 GR SR HPR	73%	9%	18%	75%	8%	< 1 %	21%
ATC 80 GR SR HPR	76%	10%	14%	79%	11%	< 1 %	20%
Comfort Serija ****						Garancija: 10 godina	
ATRS 5 DL SR HPR	14%	30%	56%	5%	12%	< 1 %	70%
ATR 05 CH SR HPR	6%	30%	64%	5%	8%	< 1 %	70%
ATR 15 CH SR HPR	39%	7%	54%	18%	5%	< 1 %	53%
ATR 20 BR SR HPR	39%	8%	53%	26%	8%	< 1 %	48%
ATR 20 CH SR HPR	28%	18%	54%	21%	8%	< 1 %	48%
ATR 35 CH SR HPR	36%	19%	45%	38%	8%	< 1 %	44%
ATR 35 BR SR HPR	35%	17%	48%	35%	12%	< 1 %	51%
ATR 50 CH SR HPR	59%	8%	33%	55%	8%	< 1 %	34%
ATR 50 BR SR HPR	59%	8%	33%	55%	8%	< 1 %	34%
PP 70 AG SR HPR	53%	20%	27%	70%	18%	< 1 %	38%
Avantagde Serija *****						Garancija: 12 godina	
LATI 05 LS SR HPR	21%	6%	74%	5%	8%	< 1 %	61%
LATI 15 LS SR HPR	22%	5%	73%	18%	6%	< 1 %	57%
LATI 35 LS SR HPR	31%	6%	63%	38%	6%	< 1 %	51%
LATI 50 LS SR HPR	38%	6%	56%	55%	7%	< 1 %	46%
AIR 75 SR HPR	52%	7%	41%	73%	9%	< 1 %	39%
AIR 80 SR HPR	42%	7%	51%	78%	8%	< 1 %	43%
Sigurnosne Folije						Garancija: 10 godina	
SCL SR PS4	81%	9%	10%	89%	8%	< 5 %	16%
SCL SR PS7	81%	9%	10%	88%	8%	< 5 %	16%
SA 05 C SR PS4	39%	7%	54%	5%	6%	< 1 %	44%
SA 15 C SR PS 4	44%	7%	49%	17%	5%	< 1 %	43%
SA 35 C SR PS 4	56%	7%	37%	38%	6%	< 1 %	34%
SA 50 C SR PS4	61%	8%	31%	52%	6%	< 1 %	29%
Specijalizirane Folije						Garancija: 5 godina	
AU 75 SR HPR	74%	9%	17%	78%	9%	< 0,1 %	21%
UV CL SR HPR	85%	8%	7%	84%	8%	< 0,1 %	14%
DL 25 BL SR HPR	35%	13%	52%	32%	10%	< 1 %	51%
DL 30 GN SR HPR	32%	18%	50%	30%	15%	< 1 %	54%
AP 60 GN SR PS	48%	22%	30%	57%	14%	< 1 %	44%
PD 10 GG SR HPR	36%	7%	57%	13%	6%	< 1 %	48%